



## AMENDMENT

(amendment based upon the provision of Article 11 of said Law)

To: Examiner of the Patent Office

1. Identification of the International Application

PCT/JP2004/008499

2. Applicant

Name: CANON KABUSHIKI KAISHA

Address: 3-30-2, Shimomaruko, Ohta-ku, Tokyo

146-8501 Japan

Country of Nationality: JAPAN

Country of Residence: JAPAN

3. Agent

Name: (8517) Patent Attorney

KATO, Nobuaki



Address: No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome,

Chiyoda-ku, Tokyo 100-0005 Japan

4. Item to be amended: Claims

5. Subject Matter of Amendment:

(1) The expression "through an SIP (Session Initiation Protocol)" should be added between "station" and "from" in the second

paragraph of the claim 1.

The expression "wherein said control means transmits a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication data" should be added to the end of the claim 1.

(2) The claim 2 should be deleted.

(3) The expression "through an SIP (Session Initiation Protocol)" should be added between "station" and "from" in the second paragraph of the claim 9.

The expression "said control means transmits a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication data" should be added to the end of the claim 9.

(4) The expression "through an SIP (Session Initiation Protocol)" should be added between "station" and "from" in the second paragraph of the claim 10.

The expression "wherein said control step is adapted to transmit a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication data" should be added to the end of the claim 10.

(5) The claim 11 should be deleted.

(6) The expression "through an SIP (Session Initiation Protocol)" should be added between "station" and "from" in the second paragraph of the claim 19.

The expression "wherein said control step is adapted to transmit a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication data" should be added to the end of the claim 19.

- (7) The claim 20 should be deleted.
- (8) The new claims 31 to 33 should be added.

6. List of Attached Documents:

- (1) Replacement sheets of pages 78, 81, 81/1, 82, 82/1, 85, 85/1, 90  
and 90/1

## CLAIMS

1. (Amended) A communication apparatus which has IP (Internet Protocol) communication means and transmits/receives communication data to/from a communication partner station discriminated by a telephone number, comprising:

IP address obtaining means for obtaining an IP address of the communication partner station through an SIP (Session Initiation Protocol) from a predetermined server based on the telephone number of the communication partner station; and

control means for transmitting/receiving on an IP network the communication data to/from the communication partner station by using the obtained IP address of the communication partner station, based on a predetermined data transmission/reception protocol,

wherein said control means transmits a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication data.

2. (Cancelled)

3. A communication apparatus according to Claim 1, further comprising:

facsimile signal communication means for performing communication of a facsimile signal; and VoIP (Voice over Internet Protocol)

8. A communication apparatus according to Claim 3, wherein said VoIP communication means is a VoIP codec for converting an analog voice signal into a digital signal.

5        9. (Amended) A communication system which includes a communication apparatus having IP (Internet Protocol) communication means and transmitting/receiving communication data to/from a communication partner station discriminated by a  
10      telephone number, comprising:

         IP address obtaining means for obtaining an IP address of the communication partner station through an SIP (Session Initiation Protocol) from a predetermined server based on the telephone number of  
15      the communication partner station; and

         control means for transmitting/receiving on an IP network the communication data to/from the communication partner station by using the obtained IP address of the communication partner station,  
20      based on a predetermined data transmission/reception protocol,

         wherein the communication partner station is a facsimile gateway, and the facsimile gateway transfers image data received from said communication  
25      apparatus according to a non-facsimile procedure to a destination communication apparatus according to a facsimile procedure, and

said control means transmits a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication data.

- 5 10. (Amended) A control method of a communication

apparatus having an IP communication means and transmitting/receiving communication data to/from a communication partner station discriminated by a telephone number, said method comprising:

5           an IP address obtaining step of obtaining an IP address of the communication partner station through an SIP (Session Initiation Protocol) from a predetermined server based on the telephone number of the communication partner station; and

10           a control step of transmitting/receiving on an IP network the communication data to/from the communication partner station by using the obtained IP address of the communication partner station, based on a predetermined data transmission/reception  
15           protocol,

          wherein said control step is adapted to transmit a transmission request message to the communication partner station after obtaining the IP address and before transmitting the communication  
20           data.

11. (Cancelled)

12. A control method according to Claim 10, further comprising:

          a facsimile signal communication step of  
25           performing communication of a facsimile signal; and

          a VoIP communication step of transmitting/receiving a frame obtained by digitally

encoding the facsimile signal output in said  
facsimile signal communication step and adding the IP



18. A control method according to Claim 10,  
wherein the communication partner station is a  
facsimile gateway, and the facsimile gateway  
transfers image data received from the communication  
5 apparatus according to a non-facsimile procedure to a  
destination communication apparatus according to a  
facsimile procedure.

19. (Amended) A control program for a  
communication apparatus having an IP communication  
10 means and transmitting/receiving communication data  
to/from a communication partner station discriminated  
by a telephone number, said method comprising:

an IP address obtaining step of obtaining an IP  
address of the communication partner station through  
15 an SIP (Session Initiation Protocol) from a  
predetermined server based on the telephone number of  
the communication partner station; and

a control step of transmitting/receiving on an  
IP network the communication data to/from the  
20 communication partner station by using the obtained  
IP address of the communication partner station,  
based on a predetermined data transmission/reception  
protocol,

wherein said control step is adapted to  
25 transmit a transmission request message to the  
communication partner station after obtaining the IP  
address and before transmitting the communication

85/1

data.

20. (Cancelled)

of the first partner station on the basis of an SIP;  
and

a control step of connecting, by using the  
telephone number of the second partner station or the  
5 IP address of the first partner station obtained in  
said obtaining step, the corresponding partner  
station, and transmitting/receiving the communication  
data to/from the corresponding partner station on the  
basis of a facsimile protocol.

10 30. A communication method of, by using an IP  
communication means, transmitting/receiving  
communication data to/from a first partner station,  
and transmitting/receiving communication data to/from  
a second partner station according to a facsimile  
15 procedure, said method comprising:

an obtaining step of obtaining a telephone  
number of the second partner station or an IP address  
of the first partner station on the basis of an SIP;  
and

20 a control step of connecting, by using the  
telephone number of the second partner station or the  
IP address of the first partner station obtained in  
said obtaining step, the corresponding partner  
station, and transmitting/receiving the communication  
25 data to/from the corresponding partner station on the  
basis of a facsimile protocol.

31. (New) A communication apparatus according to

Claim 1, wherein said control means transmits a transmission permission message in response to the transmission request message received from the communication partner station, after obtaining the IP  
5 address and before receiving the communication data.

32. (New) A control method according to Claim 10, wherein said control step is adapted to transmit a transmission permission message in response to the transmission request message received from the  
10 communication partner station, after obtaining the IP address and before receiving the communication data.

33. (New) A control program according to Claim 19, wherein said control step is adapted to transmit a transmission permission message in response to the  
15 transmission request message received from the communication partner station, after obtaining the IP address and before receiving the communication data.